# **Application for Permit to Modify (APM)**

Lease P00315 Area	a SM Block	6524 <b>Wel</b>	l Name	A004 ST	00 <b>BP</b>	00 <b>Type</b>	<b>D</b> evelopment
Application Status	Approved	Operato	<b>r</b> 03280	Freeport-	McMoRan O	il & Gas	s LLC
Pay.gov Amount: \$125.00		Agency Tracking I	D: EWL-A	APM-204945	Pay.go Tracki		26IBTTAF
General Informat	tion						
<b>API</b> 043112062600	2	Approval Dt 2	26-JUN-2	2019	Appr	oved By	John Kaiser
Submitted Dt 25-JUN	-2019 <b>W</b>	Well Status (	Complete	ed	Wate	r Depth	675
Surface Lease P003	15 <b>A</b>	Area S	M		Bloc	k	6525

### Approval Comments

Conditions of Approval:

- 1) All operations must be conducted in accordance with the OCS Lands Act (OCSLA), the lease terms and stipulations, the regulations of 30 CFR Part 250, Notices to Lessees and Operators (NTLs), the approved (revised) Application for Permit to Modify (APM/RPM), and any written instructions or orders of the District Manager.
- 2) A copy of this permit (including all attachments) must be kept on location and made available to inspectors upon request during the permitted operation.
- 3) Any casing or annuli that fails a pressure test or bubble test must be reported to the Permitting section and remediated before proceeding.
- 4) A revised PE certification is needed if (1) the plug type changes in any way including changes in cement properties, (2) any plug's setting depth (even the ones that are not required per 250.1715), changes ± 100 ' TVD, (3) the pressure test changes on any plug, (4) less cement is to be pumped, (5) more cement is to be pumped in order to isolate a hydrocarbon zone that was not anticipated in the original permit, (6) a remedial cement job is required that was not included in the original permit, or (7) any plug change that makes you deviate from the §250.1715 table.
- 5) You must have a PE certify these changes prior to these operations being performed. You must submit a revised permit with the PE certification for the revisions to this office within 72 hours.
- 6) All pressure containing equipment must be tested to the approved permitted pressure and recorded on the daily operations report. If well pressures exceed the SITP/MASP stated in the approved permit, the equipment in use must be tested at a minimum to the new observed pressure. The appropriate District must be immediately notified of this pressure change and a RPM submitted to document the change.
- 7) At the end of this operation, a tree or dry hole tree must be installed for the purpose of monitoring all non-structural casing annuli that are tied back to the surface.
- 8) Data must be submitted with the End of Operations Report (EOR) to demonstrate that the fluid left in the hole meets 30 CFR 250.1715(a)9. Corrosion inhibitor and biocide are recommended additives but not required.
- 9) Notify the Permitting Section at Least 24 hours in advance of beginning these approved operations AND of any required BOP tests AND of any plug testing or tagging.
- 10) Results of all annuli testing and plug testing must be included with the EOR.
- 11) WAR reports are due no later than noon each Wednesday.
- 12) Initial movement of CTU equipment onto the platform must be reported in eWells.
- 13) A pre-workover rig (or CTU, or HWU) inspection must be done prior to APM startup of the first well with that equipment.
- 14) The Permitting section must be notified at least 24 hours in advance of pressure testing annuli or plugs so that they might witness same. The Permitting section must also be notified of any plug tags and bubble tests for the same reason.

Correction Narrative

Page:

οf

# **Application for Permit to Modify (APM)**

<b>Lease</b> P00315	Area SM	<b>Block</b> 6524	Well Name	A004 ST	00 <b>BP</b> 00	Type Development
Application St	atus Appro	oved <b>Op</b>	erator 03280	Freeport-	McMoRan Oil	& Gas LLC
Permit Primary	Type Aban	donment Of We	ell Bore			
Permit Subtype	(s)					
Temporary Aba	ndonment					

### Operation Description

#### Procedural Narrative

The Point Arguello, OCS-P-0315, Lease has expired as of November 27, 2018. FMOG is proposing to temporarily abandon the Harvest A-4 wellbore in accordance with 30 CFR § 250.1715(a)(b). The temporary abandonment process will occur via the following:

Zonal Isolation - to be pumped as a system

- 1.) Zonal isolation will occur by setting a thru tubing cement retainer (Satisfying 30 CFR § 250.198(h)(89)) at 8,304' MD or 5' below the production packer and squeezing 40 bbls of 15.4 ppg Class G Cement from 9,710' to 8,400' MD. This operation satisfies 30 CFR § 250.1715(a)(3)(i).
- 2.) Kill weight fluid will be pumped through the tubing perforations at 8,170' MD to 1,000' MD. This operation satisfies 30 CFR § 250.1715(a)(9).
- 3.) A secondary zonal isolation will occur by tagging the top of the thru tubing cement retainer at 8,304' MD and circulating in volume of 1.2 bbls of 15.4 ppg Class G Cement up to the tubing perforations at 8,170' MD to 8,160' MD. A 1,250' balanced cement plug will be circulated in the tubing by production casing annulus with a volume of 42.3 bbls of 15.4 ppg Class G Cement, leaving cement from 8,170' to 6,920' MD. This operation satisfies 30 CFR § 250.1715(a)(3)(iii)(E).

### Secondary Cement Barrier

1.) A secondary 1,000' balanced cement plug will be circulated via tubing perforations in the tubing by production casing annulus with a volume of 33.8 bbls of 15.4 ppg Class G Cement, leaving cement from 6,000' MD to 5,000' MD. This operation will satisfies 30 CFR § 250.720(a).

### Surface Abandonment

- 2.) The tubing will be cut at 1,835' MD (1,000' BML).
- 3.) The production tree will be removed. This operation completes 30 CFR § 250.720(a).
- 4.) The production tubing will be pulled.
- 5.) A CBL will be run to the top of the cut tubing at 1,835' MD (1,000' BML) to verify the production casing is free to cut and pull.
- 6.) A 7" cast iron bridge plug (Satisfying 30 CFR  $\S$  250.198(h)(89)) will be set at 1,480' MD (645' BML) and 500' or 19.2 bbls of 15.4 ppg Class G Cement will be circulated from 1,480' MD (645' BML) to 980' MD (145' BML). This operation satisfies 30 CFR  $\S$  250.1715(a)(8).

### Testing of Cement and Annular Spaces

- 1.) All cement will be tested in accordance of 30 CFR § 250.1715(b)(2).
- 2.) All casings will be tested in accordance of 30 CFR § 250.721(d).

#### Subsurface Safety Valve

Type Installed SCSSV

Feet below Mudline 179

Maximum Anticipated Surface Pressure (psi) 1535

# **Application for Permit to Modify (APM)**

**Lease** P00315 **Block** 6524 Well Name A004 **ST** 00 **BP** 00 Type Development Operator 03280 Freeport-McMoRan Oil & Gas LLC Application Status Approved Shut-In Tubing Pressure (psi) 500 Rig Information Name ът ABS Date Coast Guard Date Type \* COIL TUBING UNIT 45016 31-DEC-2019 31-DEC-2019 Blowout Preventers --- Test Pressure ---Preventer Size Working Pressure High Low Coil Tubing 10000 250 2500 5000 2500 Wireline Date Commencing Work (mm/dd/yyyy) 01-JUL-2019 Estimated duration of the operation (days) 7 Verbal Approval Information Official Date (mm/dd/yyyy) Questions Number Question Response Response Text Is H2S present in the well? If 1 Previously submitted. YES yes, then comment on the inclusion of a Contingency Plan for this operation. 2 Is this proposed operation the N/A only lease holding activity for the subject lease? If yes, then comment. 3 Will all wells in the well bay N/A and related production equipment be shut-in when moving on to or off of an offshore platform, or from well to well on the platform? If not, please explain. 4 Are you downhole commingling two N/A or more reservoirs? 5 Will the completed interval be N/A within 500 feet of a lease or unit boundary line? If yes, then comment. 6 For permanent abandonment, will N/A casings be cut 15 feet below the

ATTACHMENTS

N/A

File Type File Description

mudline? If no, then comment.
Will the proposed operation be

covered by an EPA Discharge Permit? (Please provide permit number in comments for this

pdf Rig/Coil Tubing/Snubbing Unit BOP Schematic

question)

**U.S. Department of the Interior**Bureau of Safety and Environmental Enforcement (BSEE)

# **Application for Permit to Modify (APM)**

Lease P00315	Area SM Block 6524 Well Name A004 ST 00 BP 00 Type Development				
Application Sta	tus Approved Operator 03280 Freeport-McMoRan Oil & Gas LLC				
pdf	Proposed Wellbore Schematic				
pdf	Current Wellbore Schematic				
pdf	Procedures				
pdf	Well A-004 Categorical Exclusion Review				
	CONTACTS				
Name	Nancy Rodriguez				
Company	Freeport-McMoRan Oil & Gas LLC				
Phone Number	281-539-7640				
E-mail Address	nrodrigu@fmi.com				
Contact Descri	ption				

CERTIFICATION: I certify that information submitted is complete and accurate to the best of my knowledge. I understand that making a false statement may subject me to cr

Name and Title Date
Nancy Rodriguez, Regulatory Technician 25-JUN-2019

PAPERWORK REDUCTION ACT OF 1995 (PRA) STATEMENT: The PRA (44 U.S.C. 3501 et seq. Requires us to inform you that we collect this information to obtain knowledge of equipment and procedures to be used in drilling operations. MMS uses the information to evaluate and approve or disapprove the adequacy of the equipment and/or procedures to safely perform the proposed drilling operation. Responses are mandatory (43 U.S.C. 1334). Proprietary data are covered under 30 CFR 250.196. An agency may not conduct or sponsor, and a person is not required to respond to, a collection of information unless it displays a currently valid OMB Control Number. Public reporting burden for this form is estimated to average 11/4 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to the Information Collection Clearance Officer, Mail Stop 4230, Minerals Management Service, 1849 C Street, N.W., Washington, DC 20240.

Page:

of